



FIG. 1



HOST SYSTEM ~205-2 -205-k ~205-1 **BATTERY** BATTERY BATTERY 210~ SYSTEM POWER SUPPLY CSW1 CSW2 CSWK, 262 DSW2 DSW1 DSWk 207 240~ CHARGER CONTROLLED DC-DC CONVERTER FIG. 2 250 226 220 — POWER MANAGEMENT UNIT SELECTOR , 2,11 209~ 214~ 254~ 252 260 CHARGER 222~ 207-ACDC ပ္ပို 204 AC AC

÷. ;



• :




FIG. 5

FIG. 6

600) <				
	V	602	604	606	
		. 4		4	_
	SUPPLY MODE	NBS	SSM1 NBS	SM1 NBSSM2	
	TARGETED SUPPLY BATTER	RY A	В	A+B	
	VINP1	HIG	H HIGH	I HIGH	
	VINP2	LOV	V LOW	HIGH	
	BATTCOMP	Χ	X	HIGH	
	PBUE	LOV	V LOW	HIGH	_
	SW1	OFI	F OFF	OFF	
	SW2	ON	ON	ON	
	SW3	ON	OFF	ON	
	SW4	ON	OFF	ON	
	SW5	OF	= ON	ON	
	SW6	OFI	= ON	ON	

